

MFC cupboards

SPECIFICATION SHEET

CARCASS

Bottom, top and sides made from 18mm easy to clean scratch-resistant anti-reflective melamine faced chipboard (MFC), back panels in 8mm MFC, shelves in 25mm MFC. Panel density: 670/730 kgs per cubic meter.
Optional heavy duty 1.5mm epoxy powder coated steel shelves with lower rails to accept suspended files running front to back.


Finish options:



HINGED DOORS IN MELAMINE FACED CHIPBOARD (MFC)

Made from 18mm easy to clean scratch-resistant anti-reflective melamine faced chipboard (MFC) finished with 1.5mm matching ABS impact resistant edge. Panel density: 670/730 kgs per cubic meter.
Height/width/depth adjustable anti-corrosion treated metal hinges allowing 105° door opening. Lockable doors supplied with two folding keys.

Finish options:



HINGED DOORS IN LACQUERED MELAMINE FACED CHIPBOARD (MFC)

Made from 18mm easy to clean scratch-resistant anti-reflective melamine faced chipboard (MFC) finished with 1.5mm matching ABS impact resistant edges. The surface is coated using matt lacquers in a variety of colors. Panel density: 670/730 kgs per cubic meter.
Height/width/depth adjustable anti-corrosion treated metal hinges allowing 105° door opening. Lockable doors supplied with two folding keys.

Finish options:



Production lead time: 5 weeks exclusive of delivery time.
Apart from the 18 shown finish options any RAL color can be made to order.